



Pro navrtávání otvorů od 3/4" do 2" na plynovém a vodovodním potrubí při provozním tlaku do 12 barů

Ocelová konstrukce je chráněna proti korozi dvojitým pozinkováním. Automatická kontrola síly přítlaku při vrtání. Pracovní posun 16 cm nebo 19 cm.

Nastavitelná vrtací vzdálenost pro zvládnutí více otvorů. Bezpečnostní pojistka – vypnutí při přetížení. Použitelné v libovolné poloze. Ovládání ráčnou nebo pneumatickým či hydraulickým motorem, dodávaným na přání. Celková délka 45,5 – 51,5 cm.

Vrtací zařízení

FOR DRILLING 3/4" TO 2" HOLES ON GAS AND WATER NETWORKS OPERATING UP TO 12 bar

Steel construction protected by double zinc coating. Automatic drilling pressure control by adjustable spring. Working traverse: 16 cm or 19 cm. Variable drilling distance by means of extensions with a device for collecting the hole saw inside the machine. Safety limit switch. Usable in any position.

Operating by ratched brace or by pneumatic or hydraulic motor supplied as accessory. Overall length: 45.5/51.5 cm.

DRILLING MACHINE

**ART.
230**

Toto zařízení je určeno pouze pro malé průměry otvorů, ale s nastavitelnou volbou a s posunem do strany pomocí teleskopické konstrukce. Celé zařízení je uloženo do pevné ocelové bedny, včetně ráčny, nástrojů a vrtacích fréz typu A pro ocel a litinu.

This machine Art. 230 even if with small dimension offers great features due to its device for the release of the top part of the machine, thus allowing to use extensions when the standard traverse is shorter than required. Supplied complete with a strong steel box, ratched brace and tools, high speed steel hole saw cutters A Type for steel, cast and ductile.

Náhradní díly / SPARE PARTS

- Art. 101 Sklíčidlo pro frézy od 3/4" do 1"1/4.
Mandrel for 3/4" up to 1.1/4" hole saw cutters.
- Art. 102 Sklíčidlo pro frézy od 1"1/2 do 2".
Mandrel for 1.1/2" up to 2" hole saw cutters.
- Art. 103 Prodloužení cm. 5 / Extension 5 cm.
- Art. 104 Pilová fréza typ AV pro ocel a litinu
AV Type hole saw cutter for steel and cast iron.
- Art. 105 GRC typ pilové frézy pro litinu s vnitřním cementováním
GRC Type hole saw cutter for cast iron with internal cement mortar.
- Art. 106 PE typ pilové frézy pro plasty
PE Type hole saw cutter for polyethylene.
- Art. 214 LX/CT typ pilové frézy pro litinu
LX/CT Type hole saw cutter for cast iron.
- Art. 301 Závitový adapter od DN 3/4" do DN 2" standardní (bez odvodušnění)
Threaded adaptor for 3/4" up to 2" as standard without vent fitting
- Art. 301/A Závitový adapter od DN 3/4" do DN 2" (s odvodušněním)
Threaded adaptor for 3/4" up to 2" with vent fitting.

